

# SPECIAL PACKAGING INSTRUCTION

Form Approved XTH  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, Va 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503. Please do not return your form to either of these addresses.

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE 13230E3650 97403 DOGBONE ASSEMBLY		2. CODE INDENT 19207		3. SPI NO. AK 13804852	
4. NATIONAL STOCK NO. 2590-01-380-4852		5. DATE OF DRAWING 01-09-96		6. REVISION	
7. QUP 001	8. ICQ NONE	9. UNIT PACK WT. (LB) 250.0	10. UNIT PACK CUBE (CU. FT.) 4.861	11. UNIT PACK SIZE (INCHES) 30.0 X 20.0 X 14.0	
12. PRESERVATION		18. STE	19. REQ	20. DESCRIPTION	
a. LEVEL A MIL-P-116 METHOD I		1B		PRESERVATIVE: MIL-C-16173, GRADE 4,	
b. LEVEL B NOT APPLICABLE		2C		CONTAINER: PPP-B-621, STYLE 4, CLASS 2,	
13. CLEANING MIL-P-116 PROCESS C-1					
14. DRYING MIL-P-116					
15. PACKING					
a. LEVEL A MIL-STD-2073					
b. LEVEL B NOT APPLICABLE					
16. MARKING MIL-STD-129 AND NOTE D					
17. NOTES/DRAWING					
A. QUALITY ASSURANCE PROVISIONS: PRESERVATION AND PACKING SHALL BE INSPECTED IN ACCORDANCE WITH MIL-STD-2073.					
B. APPLY PRESERVATIVE TO UNPAINTED EXTERIOR METALLIC SURFACES.					
C. BLOCKING, BRACING, CUSHIONING, AND IMMOBILIZATION OF THE ITEM WITHIN THE CONTAINER SHALL MEET THE REQUIREMENTS OF MIL-P-116, INCLUDING THE APPLICABLE ROUGH HANDLING TEST. THE UNIT CONTAINER IS THE SHIPPING CONTAINER. A PPP-B-601, OVER SEAS TYPE CONTAINER MAY BE USED AS AN ALTERNATE CONTAINER.					
D. THE IMPROVED DOGBONE, PART NUMBER 1323E3625, IS MAGNETIC. APPROPRIATE SHIELDING MAY BE REQUIRED TO ENSURE THE MAGNETIC FIELD STRENGTH AT A DISTANCE OF 4.6 M (15 FT) FROM ANY POINT ON THE SURFACE OF THE ASSEMBLED CONSIGNMENT DOES NOT EXCEED 0.418 A/M (0.00525 GAUSS), OR PRODUCES A MAGNETIC COMPASS DEFLECTION OF 2 DEGREES OR MORE. IF SHIELDING IS REQUIRED, SEE MIL-S-4473, SHIELDING OF MAGNETRON TUBES AND MAGNETS FOR AIR SHIPMENT.					
UNIT PACK WT,CU, AND SIZES ARE ESTIMATED AND ARE PROVIDED FOR INTERNAL GOVERNMENT PURPOSES ONLY.					